

AD- typ francouzský standard pro distribuci



velikost	jm. proud (A)	jm. napětí (kV)	kat. číslo	ref. číslo	balení
10 x 38	15	440	10AD44V15	V216149J	10
14 x 51	15	440	14AD44V15	E222966J	10
14 x 51	30	440	14AD44V30	M200755J	10
22 x 58	15	440	22AD44V15	M222973J	10
22 x 58	30	440	22AD44V30	V200762J	10
22 x 58	45	440	22AD44V45	K201305J	10
22 x 58	60	440	22AD44V60	T201819J	10
00	45	440	00AD44V45	J223430J	10
00	60	440	00AD44V60	P223435J	10
00	90	440	00AD44V90	X223442J	10
10 x 38 Neutral			FRN1038	R211569J	10
14 x 51 Neutral			FRN1451	L228032J	10
22 x 58 Neutral			FRN2258	M228033J	10

For cylindrical nozzle fuses: please enquire.

CNL pojistky pro nízkonapěťové baterie



jm. napětí (V)	jm. proud (A)	pojistkový spodek kat. číslo	pojistkový spodek ref. číslo	jm. napětí (V)	jm. proud (A)	pojistkový spodek kat. číslo	pojistkový spodek ref. číslo	
32VAC & VDC	35	CNL35 DIN	T216332E	130VAC / 75VDC PdC: 2500A	10	CNN10 DIN	E228831	
	40	CNL40 DIN	L217360E		35	CNN35 DIN	F228832	
	50	CNL50 DIN	A218385E		40	CNN40 DIN	G228833	
	60	CNL60 DIN	E219424E		50	CNN50 DIN	H228834	
	80	CNL80 DIN	Y219947E		60	CNN60 DIN	J228835	
	100	CNL100 DIN	K201995E		80	CNN80 DIN	K228836	
	125	CNL125 DIN	K211218E		90	CNN90 DIN	L228837	
	130	CNL130 DIN	A211738E		100	CNN100 DIN	M228838	
	150	CNL150 DIN	J212252E		125	CNN125 DIN	N228839	
	175	CNL175 DIN	W212769E		150	CNN150 DIN	P228840	
	PdC: 2500A	200	CNL200 DIN		J213287E	175	CNN175 DIN	Q228841
		225	CNL225 DIN		A213785E	180	CNN180 DIN	N229874
		250	CNL250 DIN		J214299E	200	CNN200 DIN	R228842
		275	CNL275 DIN		J214805E	225	CNN225 DIN	S228843
		300	CNL300 DIN		L215313E	250	CNN250 DIN	T228844
		325	CNL325 DIN		P215822E	275	CNN275 DIN	V228845
350		CNL350 DIN	X216841E		300	CNN300 DIN	W228846	
400		CNL400 DIN	T217873E		325	CNN325 DIN	X228874	
500		CNL500 DIN	Q218905E		350	CNN350 DIN	Y228848	
					400	CNN400 DIN	Z228849	
			500		CNN500 DIN	A228850		
			600		CNN600 DIN	B228851		
			700		CNN700 DIN	C228852		
			800		CNN800 DIN	D228853		
								130VAC / 48VDC PdC: 2500A @ 48VDC

rozměry

	A mm	B mm	C mm	D mm	E mm
CNL DIN/CNN DIN	82	60	23 max.	20	11

